

								
Nome	BT 400	BT 800	LSP 1000-EB-VP	LSP 1200-DL-VP	LSP 1600-DL-VP	LSP 3000	LSP 5000	LSP 7000
Campo di impiego	0÷400 bar	0÷800 bar	0÷1000 bar	0÷1200 bar	0÷1600 bar	0÷3000 bar	0÷5000 bar	0÷700 bar
Liquido	Acqua o olio	Acqua o olio	Olio minerale	Olio minerale	Olio minerale	Olio	Olio	Olio
Capacità	73 cm ³	30 cm ³	400 cm ³	400 cm ³	400 cm ³	250 cm ³	250 cm ³	250 cm ³
Prese di pressione	2 x 1/2" G	2 x 1/2" G	2 x 1/2" BSP F	2 x 1/2" BSP F	2 x 1/2" BSP F	2 x M16 X 1,5 M	2 x M16 X 1,5 M	2 x M16 X 1,5 M
Volume spostato per giro	2 cm ³	0,7 cm ³	0,1 cm ³	0,1 cm ³	0,1 cm ³	0,15 cm ³	0,08 cm ³	0,08 cm ³
Dimensioni	450 x 360 x 300 mm	650 x 360 x 330 mm	600 x 280 x 220 mm	600 x 300 x 240 mm	600 x 300 x 240 mm	460 x 445 x 265 mm	460 x 445 x 265 mm	460 x 445 x 265 mm
Peso	14 kg	18 kg	8,5 kg	9,9 kg	9,9 kg	33,5 kg	32,5 kg	32,5 kg
Versioni speciali	BT 400-OX impiego con ossigeno <hr/> BT 400-V impiego con liquidi aggressivi <hr/> BT 400+ impiego fino a 600 bar		LSP 1000-EB-VP-S impiego con liquidi aggressivi	LSP 1200-DL-VP impiego con liquidi aggressivi	LSP 1600-DL-VP impiego con liquidi aggressivi			